



Unicable II™

2-way splitter, 5-2400MHz

IDLU-USP105-OU020-OBT

Item: 5660



This Unicable™ splitter supports bidirectional distribution of DC and RF signals. It enables control signals and DiSEqC commands sent from the Set Top Boxes to the LNB as well as DiSEqC commands sent from the LNB to the Set Top Box. This high-quality Unicable™ splitter features low insertion loss, high RF isolation between the output ports and allows greater flexibility in single home or MDU installation scenarios. Typically, the splitter would be installed at a central location (i.e. roof's attic) with separate coax cables stretched inside the house/apartment to each Set Top Box. The Unicable splitter embeds protective diodes to guarantee DC isolation between connected set top boxes.

For more information on the Unicable II™ technology and its advantages please refer to: www.inverto.tv/what-is-unicable-2

For more information on the SatPal™ technology and its advantages please refer to: www.inverto.tv/satpal

Main Features:

- Low insertion loss, high return loss and port isolation for satellite and CATV applications
- Unicable compatible
- RF shielded Zinc die cast housing (Class A)
- Grounding terminal
- Supplied with two mounting screws
- Light weight and compact size



Technical data

Frequency range	5 MHz - 2400 MHz
Inputs	1x F-type, female
Output	2x F-type, female
Insertion loss	<4 dB (5 MHz ~ 40 MHz) <5 dB (40 MHz ~ 860 MHz) <5.5 dB (860 MHz ~ 1750 MHz) <6 dB (1750 MHz ~ 2400 MHz) 20 dB min.
Isolation between ports	10 dB min.
Input return Loss	10 dB min.
Output return loss	35 V max., up to 1 A pass through current towards LNB
DC & 22 kHz pass from Output to Input	bi-directional for DiSEqC commands
Steering diodes	Yes
Impedance	75 Ω
CE, RF screening Class	Class A
Operating temperature	-30° C ~ +60° C
Weight	36 g
Dimensions (W x D x H)	55.5 mm x 47.5 mm x 16 mm

Logistical info

Quantity per carton	50
Carton dimensions (W x D x H)	15 cm x 15 cm x 15 cm
Carton weight	2.0 kg

